Pipe Tape White

Product Description:

AmCon epoxy Pipe Tape is a patented, fiberglass cloth pre – impregnated with a resin that can be activated by water. Packaged in a hermetically sealed foil po does not require any measuring or mixing. This system enables you to repair almost any pipe in minutes, while saving you thousands in parts and labor.

With an setting time of only 30 minutes (75 F) it is excellent solution for reducing downtime. Offering excellent adhesion to Steel, SS, PVC, FRP, Clay, Concrete, Rubber, etc, it is amazingly versatile. Am Com epoxy Pipe Tape is safe to use, non – toxic, non – combustible and odorless. This repair cannot only restore a pipe to its original PSI rating, but can actually make the repair area stronger than the original pipe.

Physical Properties

Finished Repair Pressure Rating, (8 layers with patch),	psi 600 – 1000
Temperature Resistance, continuous	300°F (149°C)
Shelf Life	2 years
Tensile Strength, ASTM D 638 Type I – 8 ply, psi	36,448
Flexural strength, ASTM D 790 Type I – 8 ply, psi	26,100
Compressive Strength, ASTM D 695 – 8 ply, psi	8,072
Dielectric Strength, volts	16,060
Hazards	Non- toxic, non-combustible, and safe to use

Chemical Resistance

Excellent, refer to product data sheet for specifics

ASTM D 543, Test Period 2 Months @ 73F

Solution Tested	Type of Change
Sulfuric Acid 10%	None
Sulfuric Acid 50%	None
Hydrochloric Acid 10%	None
Hydrochloric Acid 50%	None
Sodium Hydroxide Solution 20%	None
Gasoline	None
Toluene	None
Xylene	None
Mineral Spirits	None
Nitric Acid 50%	Blistering
Distilled Water	None

Manufactured in: USA

Supplied by: FITCON (S) PTE LTD

51, Bukit Batok Crescent, # 07- 08, Unity Center, Singapore 658077 Tel: (65) 64730048, Fax: (65) 68985005, H/P: 94575123, E-mail: fitcon@patronicsgroup.com